

Architectural Terrazzo

Product (name)	Size (mm)	Thickness (mm)	Edge
SLABS XL	3000 mm by 1200 mm	20 / 30 / 50 / 80	not chamfered
Pavers (ii)	900 x 600	30 / 45	not chamfered
Pavers (ii)	400 x 400	30 / 45	not chamfered
Pavers (iii)	1000 x 300	30 / 45	not chamfered

Finish	Slip Rating
Honed	R9
Honed	R10
Sand Blasted	R11
Polished	
Brushed	

Specifications

Product type	Terrazzo
Manufactured to	EN 13748-1
Flexural Strength	Avg 8 N/mm ²
Slip/Skid Risk	Depending on surface texture required
Tolerances on dimensions	Length ±2mm, Width ±2mm, Thickness ±3mm on cut to size elements
Abrasion Resistance	≤ 30 cm ³ / 50 cm
Water Absorption	≤ 5 %
Density	2.500 / 2600 kg/m ³
External Fire Performance	Deemed to satisfy 2000/553/EC
Reaction to Fire	Class A1
Energy used	100% renewable energy
Water used	100% from our water harvesting reservoirs and sustainable resources
Recycled content	≈ 10%
Recyclable	100% of this product can be recycled.
Manufacturing & Delivery	Hal Far, Malta