

Fina Paver Collection

Product (name)	Size (mm)	Thickness (mm)	Edge
Pavers (i)	400 x 400	30 / 50 / 80	not chamfered
Pavers (ii)	900 x 600	30 / 50 / 80	not chamfered

Colours: Beige Crema, Grigio, Basalto, Marone

Finish	Slip Rating	Thickness (mm)	Loading
Hammered Brushed	> 35 PTV	30 mm	Pedestrian with Emergency Vehicles *
Brushed	< 35 PTV	50 mm	Pedestrian with Emergency Vehicles *
		80 mm	Light Traffic *

*Paving Subbase shall be engineered to accommodate the paving loading above

Specifications

Product type	Reconstituted stone pavers
Manufactured to	BS EN 1339:2003
Efflorescence	Minimum 12 hour environmentally controlled curing to significantly reduce the possibility of efflorescence
Strength	Less than 50mm deep- Typical tensile splitting strength of >3.5MPa 50mm or greater- Typical tensile splitting strength of >5MPa (Class 3)
Slip/Skid Risk	Depending on surface texture required
Installed to	BS 7533-4:2006
Tolerances on dimensions	Length ± 2 mm, Width ± 2 mm, Thickness ± 3 mm
Abrasion Resistance	Class 3
Durability (Freeze-thaw)	Class 3
External Fire Performance	Deemed to satisfy 2000/553/EC
Reaction to Fire	Class A1
Applications	Refer to BS 7533 for the correct sub-base design for your application
Energy used	100% renewable energy
Water used	100% from our water harvesting reservoirs and sustainable resources
Recycled content	$\approx 30\%$
Recyclable	100% of this product can be recycled.
Manufacturing & Delivery	Hal Far, Malta